

Description

- effective emulsifier and cleaning agent in anhydrous, highly concentrated bath and shower preparations with a high oil content,
- clear formulations are obtained with polar vegetable oils, such as castor oil, regardless of the mixing ratio,
- less polar oils, e.g. olive oil or sunflower oil, as well as paraffin oil, require the

- addition of a coemulsifier to achieve clarity,
- · foaming agent,
- compatible with anionic, non-ionic and amphoteric surfactants,
- component of liquid detergent concentrates intended for l&l and household.

Application

- · shower oils,
- · gentle foaming cleansers,
- · cleansing emulsions,
- exfoliating cleansers.

in line with cosmetic trends

guarantee the consumer satisfaction



improvement of
Personal Care formulations

innovative product

value for money



SULFOROKAnol L385/1T

TIPA Laureth Sulfate (And) Propylene Glycol

Chemical name	Alcohols C12-14, ethoxylated (3 EO), sulfated, triisopropanolamine salts and propylene glycol		
INCI name	TIPA Laureth Sulfate (and) Propylene Glycol		
CAS number	107600-36-2, 57-55-6		
Function	Base surfactant, foaming agent		
Technical requirements	Appearance at temperature (20÷25)°C	viscous liquid	
	Active substance, %(mm)	82 ÷ 92	
	pH of 2% solution	6.0 ÷ 8.0	
	lodine colour number, 50% (m/m) in propylene glycol solution at temperature (20÷25)°C	max. 4	
	1,4-dioxane, ppm	max. 25	
General data	1,2-Propylene Glycol, % (m/m)	below 10	
	Viscosity at 25°C, cP	3000 ÷ 8000	
	Density at 20°C, g/mL	approx. 1.06	
	Solidification point, °C	approx10	

Shower oil

Phase	INCI name	Brand name	Concentration [%]	Function
Α	Helianthus Annuus Seed Oil		54.50	emollient
Α	Tocopheryl Acetate		1.00	active
Α	TIPA Laureth Sulfate, Propylene Glycol	SULFOROKANOL L385/1T	20.00	surfactant
В	Laureth-2	ROKAnol Lk2	24.00	surfactant
В	Parfume		0.50	fragrance

Appearance	visual method	slightly yellowish
		viscous liquid
Viscosity [cP]	Brookfield LV, spindle: 34, speed: 2,5 RPM, T:25°C	< 100
Stability	1 month in 5°C, 20°C, 40°C.	confirmed

Procedure:

- 1. In a main vessel combine ingredients from phase A. Mix until uniform.
- **2.** Combine ingredients from phase B in a separate vessel and mix until uniform.
- **3.** Add ingredients from phase B to phase A while mixing. Mix until uniform.





PCC Exol SA
Sienkiewicza 4
56-120 Brzeg Dolny, Poland
products@pcc.eu

Please visit our capital group business platform

www.products.pcc.eu



April 2025

The information in the catalogue is believed to be accurate and compiled to the best of our knowledge; however, it should be considered as introductory only. Detailed information about our products is available in TDS and MSDS.

he suggestions for product applications are based on our best knowledge.

The responsibility for the use of products in conformity or otherwise with the suggested application, and for determining product suitability for the user's own purposes rests with the user.

All copyright and trademark rights, as well as other intellectual and industrial property rights and the resulting rights to use this publication and its contents have been transferred to PCC Rokita SA or PCC EXOL SA or its licensors. All rights reserved. Users/readers are not entitled to reproduce this publication in whole or in part, nor are they entitled to reproduce if (excluding reproduction for personal use) or to transfer it to third parties.

Permission to reproduce it for personal use does not apply to data used in other publications, electronic information systems,