

EXOemul EM260

TECHNICAL SPECIFICATION	PRODUCT
NUMBER	STW: EX/415/6
DATE	2020-04-07
CHEMICAL NAME	A mixture of anionic and nonionic surfactants
TECHNICAL REQUIREMENTS	<p>Appearance at temperature (20÷25)°C..... yellow to light brown liquid with a tendency to becomes turbid which disappears after heating</p> <p>pH of 1% solution6.0 ÷ 8.0 (PN-EN 1262:2004, solution C, at 20°C)</p> <p>Colour at Gardner scale at 25°C max 10 (PN-EN ISO 4630-1:2006)</p>
INFORMATIVE DATA*	<p>Solubility in water weak</p> <p>Other solvents n-octanol, ethyl ether, acetone, methanol Low aliphatic alcohols</p> <p>Density at 20°C, g/mL 0.950 ÷ 1.100</p> <p>Viscosity at 20°C, cP approx.. 2300</p> <p>Odour characteristic</p> <p>Solidification point, °C approx.-15</p> <p>Flash point, °C approx. 110</p>

* These informative data are not technical requirements and cannot form the basis for any claims.

USE EXOemul EM260 is a mixture of surfactants with emulsifying properties of based on rapeseed oil methyl esters formulations. Product shows a high efficiency of formulation emulsifying and provides stability of emulsions.

PACKAGING Polyethylene drums or containers and other packaging as agreed with the customer.

STORAGE	Store in tightly closed containers in a roofed areas, at temperature of 0° to 40°C. During storage, a precipitate may form in the product, which dissolves upon heating.
SHELF LIFE	12 months from the date of manufacture.
TRANSPORTATION	Limitations resulting from ADR, RID, IMDG and ICAO/IATA regulations apply. Covered means of transport recommended. UN Number: UN1993 UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (butan-1-ol) Transport hazard class: 3 Packing group: III
CLASSIFICATION AND LABELLING	This technical specification is applicable only if accompanied by the Safety Data Sheet in force. Pursuant to statutory requirements, only the Safety Data Sheet includes updated safety information.

The information contained herein is provided in good faith, based on our state of the art knowledge and experience. We reserve the right to amend this Technical Specification as a result of technological progress and product development by the manufacturer.

This product is intended for the purposes specified herein, for industrial and professional use. To use the product for purposes other than indicted herein, please contact PCC EXOL SA for consultation sending an e-mail to: industrial.application@pcc.eu

We cannot assume any liability for the use and application of our products, technical assistance and information provided (whether verbal, written or by way of product evaluations), including any suggested formulations and recommendations.

Therefore, it is imperative that you test our products, technical assistance and information provided to determine to your own satisfaction whether they are suitable for your needs, production, your intended uses and applications. Such analysis adopted to the conditions of the use and application should include at least application tests, technical feasibility of the suggested solutions, taking into account safety requirements, health and environmental issues.

Unless otherwise specified in writing, our products are offered under our applicable Standard Terms and Conditions of Sale available on our website. Any information, including technical assistance, is provided without warrant and can change at any time without notice. The parties explicitly agree that the Customer accepts and explicitly releases us from any liability in tort, contract or otherwise, for any loss or damage arising from the use of our products, information or technical assistance. Any declarations and recommendations other than stated herein are not valid or binding. Nothing in this document is intended to be a recommendation to use any product in violation of patent claims concerning material of intended use.