

EXOlub L6

TECHNICAL SPECIFICATION	PRODUCT
NUMBER	STW: EX/1669/01
DATE	2023-04-05
CHEMICAL NAME	Mixture
TECHNICAL REQUIREMENTS	Appearance at temperature 40°C liquid Kinematic viscosity 40°C, mm ² /s 41 ÷ 55 (ASTM D445-19) Density at 15°C, g/mL..... 1.13 ÷ 1.15 (PN-EN ISO 3675:2004) Pour point, °C below -30 (ASTM D97)
INFORMATIVE DATA*	Solubility in water soluble Kinematic viscosity 100°C, mm ² /s approx. 7 Solidification point, °C below -30 pH of 5% solution 5 ÷ 7 Viscosity index approx. 110
	* These informative data are not technical requirements and cannot form the basis for any claims.
USE	EXOlub L6 is used as a component of hydraulic fluids and metalworking fluids.

PACKAGING	Stainless steel tanks or road tankers, polyolefin containers or other packaging agreed with the recipient.
STORAGE	Store in closed containers in roofed rooms at temperatures up to 40°C. Protect against weather conditions and direct sunlight. During the storage of the product, over time, it may delaminate (the product is cloudy in the lower part and clear in the upper part). The product, after heating to (40 ÷ 50)°C and mixing, returns to its previous form.
SHELF LIFE	Shelf life is 12 months from the date of manufacture. After this period, it can be used after checking the compliance of parameters with technical requirements.
TRANSPORTATION	This product is not regulated for carriage according to ADR/RID, IMDG, ICAO/IATA. Covered means of transport recommended.
CLASSIFICATION AND LABELLING	This technical specification is applicable only if accompanied by the Safety Data Sheet in force. Pursuant to statutory requirements, only the Safety Data Sheet includes updated safety information.

The information contained herein is provided in good faith, based on our state of the art knowledge and experience. We reserve the right to amend this Technical Specification as a result of technological progress and product development by the manufacturer.

This product is intended for the purposes specified herein, for industrial and professional use. To use the product for purposes other than indicated herein, please contact PCC EXOL SA for consultation sending an e-mail to: industrial.application@pcc.eu

We cannot assume any liability for the use and application of our products, technical assistance and information provided (whether verbal, written or by way of product evaluations), including any suggested formulations and recommendations.

Therefore, it is imperative that you test our products, technical assistance and information provided to determine to your own satisfaction whether they are suitable for your needs, production, your intended uses and applications. Such analysis adopted to the conditions of the use and application should include at least application tests, technical feasibility of the suggested solutions, taking into account safety requirements, health and environmental issues.

Unless otherwise specified in writing, our products are offered under our applicable Standard Terms and Conditions of Sale available on our website. Any information, including technical assistance, is provided without warrant and can change at any time without notice. The parties explicitly agree that the Customer accepts and explicitly releases us from any liability in tort, contract or otherwise, for any loss or damage arising from the use of our products, information or technical assistance. Any declarations and recommendations other than stated herein are not valid or binding. Nothing in this document is intended to be a recommendation to use any product in violation of patent claims concerning material of intended use.