

ROKAmin SR5

TECHNICAL SPECIFICATION	PRODUCT
NUMBER	STW: EX/192/5
DATE	2026-07-17
CHEMICAL NAME	Amines, C16-18 alkyl, ethoxylated
TECHNICAL REQUIREMENTS	Appearance at temperature (20÷25)°liquid light brown to brown colour Amine value, mgKOH/g 105 ÷ 110 (LA/2154) Water, %(m/m)max 1 (PN-ISO 760:2001, direct method solvent: mixture of 35 mL of Solvent G + 5g of benzoic acid)
INFORMATIVE DATA*	Molecular weight, g/molapprox. 500 Solubility in watersparingly soluble, creates a turbid solution Other solvents ethanol, chloroform, isopropanol Density at 25°C, g/mLapprox. 0.95 Boiling point, °Cabove 200 (with decomposition) Flash-point, °Cabove 130 Solidification point, °Cbelow 15 Odourcharacteristic

* These informative data are not technical requirements and cannot form the basis for any claims.

USE	ROKAmin SR5 is used as an emulsifier and fibre colouring equalizing agent.
-----	--

PACKAGING	Cisterns or tanker trucks made of acid resistant steel with heating elements, polyolefin containers with a capacity or containers marked with an appropriate UN label.
STORAGE	Store in closed containers made of polyester or acid resistant steel fitted with heating elements; store in closed polyolefin containers. Maximum storage temperature of 40°C.
SHELF LIFE	Guaranteed period of stability: 24 months from the date of manufacture.
TRANSPORTATION	This product is regulated for carriage according to ADR/RID, IMDG, ICAO/IATA. UN Number: 3082 UN Proper shipping name; ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Amines, C16-18 alkyl, ethoxylated) Transporthazard class(es): 9 Packing group: III
CLASSIFICATION AND LABELLING	This technical specification is applicable only if accompanied by the Safety Data Sheet in force. Pursuant to statutory requirements, only the Safety Data Sheet includes updated safety information.

The information contained herein is provided in good faith, based on our state of the art knowledge and experience. We reserve the right to amend this Technical Specification as a result of technological progress and product development by the manufacturer.

This product is intended for the purposes specified herein, for industrial and professional use. To use the product for purposes other than indicated herein, please contact PCC EXOL SA for consultation sending an e-mail to: industrial.application@pcc.eu

We cannot assume any liability for the use and application of our products, technical assistance and information provided (whether verbal, written or by way of product evaluations), including any suggested formulations and recommendations.

Therefore, it is imperative that you test our products, technical assistance and information provided to determine to your own satisfaction whether they are suitable for your needs, production, your intended uses and applications. Such analysis adopted to the conditions of the use and application should include at least application tests, technical feasibility of the suggested solutions, taking into account safety requirements, health and environmental issues.

Unless otherwise specified in writing, our products are offered under our applicable Standard Terms and Conditions of Sale available on our website. Any information, including technical assistance, is provided without warrant and can change at any time without notice. The parties explicitly agree that the Customer accepts and explicitly releases us from any liability in tort, contract or otherwise, for any loss or damage arising from the use of our products, information or technical assistance. Any declarations and recommendations other than stated herein are not valid or binding. Nothing in this document is intended to be a recommendation to use any product in violation of patent claims concerning material of intended use.