ABSNa 30

TECHNICAL SPECIFICATION	**PRODUCT**
NUMBER	**STW: EX/380/2**
DATE	2019-06-10
CHEMICAL NAME	Benzenesulfonic acid, C10-13 alkyl derivative, sodium salt
TECHNICAL REQUIREMENTS	Appearance at temperature (20÷25)˚C.....clear or turbid liquid pH of 2% active substance solution.....10 ÷ 11 (PN-EN 1262:2004, solution A, at 25ºC) Sodium alkylbenzenesulphonate, %(m/m).....30 ÷ 2 (PN-ISO 2271:2000) Colour of 5% active substance solution in Hazen scale.....max 100 (ASTM D1209-05 (2019), visual method) Unsulphonated substances calculated as active substance, % (m/m) .....max 3 (MB-0019) Sodium sulphate (VI), % (m/m) .....max 1 (MB-0031)
INFORMATIVE DATA*	Molecular weight, g/mol.....340 ÷ 348 Solubility in water ..... unlimited Other solvents..... low aliphatic alcohols Density at 25˚C, g/mL.....approx. 1.05 Odour..... weak, characteristic

* These informative data are not technical requirements and cannot form the basis for any claims.

USE

Anionic surfactant used as a component of liquid and powder washing and cleaning agents. ABSNa 30 exhibits strong foaming, wetting and emulsyfing properties. This product can be also used in industrial applications.

PCC Exol SA
ul. Sienkiewicza 4
56-120 Brzeg Dolny
Poland
www.pcc-exol.eu

PACKAGING	Cisterns or tanker trucks made of acid resistant steel with heating elements, polyolefin containers with a capacity, containers or other packaging as agreed with the customer.
STORAGE	Store in closed vessels made of acid resistant steel or other corrosion-resistant material fitted with heating elements and a mixer or a circulating pump, store in closed polyolefin containers. Maximum storage temperature of 50°C. Copper and its alloys may cause colouring of the product.
SHELF LIFE	Guaranteed period of stability: 12 months from the date of manufacture.
TRANSPORTATION	**Limitations resulting from ADR, RID, IMDG and ICAO/IATA regulations do not apply.**
CLASSIFICATION AND LABELLING	This technical specification is applicable only if accompanied by the Safety Data Sheet in force. Pursuant to statutory requirements, only the Safety Data Sheet includes updated safety information.

The information contained herein is provided in good faith, based on our state of the art knowledge and experience. We reserve the right to amend this Technical Specification as a result of technological progress and product development by the manufacturer.

This product is intended for the purposes specified herein, for industrial and professional use. To use the product for purposes other than indicted herein, please contact PCC EXOL SA for consultation sending an e-mail to: industrial.application@pcc.eu

We cannot assume any liability for the use and application of our products, technical assistance and information provided (whether verbal, written or by way of product evaluations), including any suggested formulations and recommendations.

Therefore, it is imperative that you test our products, technical assistance and information provided to determine to your own satisfaction whether they are suitable for your needs, production, your intended uses and applications. Such analysis adopted to the conditions of the use and application should include at least application tests, technical feasibility of the suggested solutions, taking into account safety requirements, health and environmental issues.

Unless otherwise specified in writing, our products are offered under our applicable Standard Terms and Conditions of Sale available on our website. Any information, including technical assistance, is provided without warrant and can change at any time without notice The parties explicitly agree that the Customer accepts and explicitly releases us from any liability in tort, contract or otherwise, for any loss or damage arising from the use of our products, information or technical assistance. Any declarations and recommendations other than stated herein are not valid or binding. Nothing in this document is intended to be a recommendation to use any product in violation of patent claims concerning material of intended use.

PCC Exol SA
ul. Sienkiewicza 4
56-120 Brzeg Dolny
Poland
www.pcc-exol.eu