

ROKAnol® T6PF

TECHNICAL SPECIFICATION	PRODUCT
NUMBER	STW: EX/748/5
DATE	2026-07-06
CHEMICAL NAME	Macrogol cetostearyl ether
TECHNICAL REQUIREMENTS	Samenesscomplies with A, B,C,D,E tests (Ph. Eur. 12+ Suppl.) Appearance at (20÷25)°C yellowish – white or white wax (Ph. Eur. 12+ Suppl.) Solution appearance.....≤ colour of the comparative solution BY₅ (Ph. Eur. 12+ Suppl.) Hydroxyl value, mg KOH/g100 ÷ 134 (Ph. Eur. 12+ Suppl.) Acidity value, mg KOH/g..... ≤ 1.0 (Ph. Eur. 12+ Suppl.) Alkalinity, mL ≤ 0.5 (Ph. Eur. 12+ Suppl.) Saponification, mg KOH/g ≤ 3.0 (Ph. Eur. 12+ Suppl.) Iodine number, gI₂/100g ≤ 2.0 (Ph. Eur. 12+ Suppl.) Total ash, % (m/m)..... ≤ 0.2 (Ph. Eur. 12+ Suppl.) Water, % (m/m) ≤ 3.0 (Ph. Eur. 12+ Suppl.) Ethylene oxide, ppm..... ≤ 1 (LA/2141) Dioxane, ppm ≤ 10 (LA/2141) Water solubility (20÷25)°C..... hardly soluble (Ph. Eur. 12+ Suppl.) Methylene chloride solubility (20÷25)°C.....soluble (Ph. Eur. 12+ Suppl.) Ethanol 96% water solution solubility (20÷25)°Csoluble (Ph. Eur. 12+ Suppl.)
INFORMATIVE DATA*	-

* These informative data are not technical requirements and cannot form the basis for any claims.

USE

The product meets the quality requirements specified in the current edition of the European Pharmacopoeia. It is a non-ionic emulsifier used to produce stable oil-in-water (O/W) emulsions in cosmetics, and dermocosmetics.applications.

PACKAGING	Packaging as agreed with the customer.
STORAGE	ROKAnol T6PF is stable for 2 years when stored in original, tightly closed containers. It is recommended that the ambient temperature during long-term storage is between 5°C and 25°C, with the extreme acceptable range being between 0°C and 30°C. Storage at higher temperatures is only possible for a short time.
SHELF LIFE	24 months from the date of manufacture.
TRANSPORTATION	This product is regulated for carriage according to ADR/RID, IMDG, ICAO/IATA UN number: 3077 UN Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Alcohols, C16-18, ethoxylated) Transport hazard class(es): 9 Packing group: III
CLASSIFICATION AND LABELLING	This technical specification is applicable only if accompanied by the Safety Data Sheet in force. Pursuant to statutory requirements, only the Safety Data Sheet includes updated safety information.

The information contained herein is provided in good faith, based on our state of the art knowledge and experience. We reserve the right to amend this Technical Specification as a result of technological progress and product development by the manufacturer.

This product is intended for the purposes specified herein, for industrial and professional use. To use the product for purposes other than indicated herein, please contact **PCC EXOL SA** for consultation sending an e-mail to: industrial.application@pcc.eu.

We cannot assume any liability for the use and application of our products, technical assistance and information provided (whether verbal, written or by way of product evaluations), including any suggested formulations and recommendations.

Therefore, it is imperative that you test our products, technical assistance and information provided to determine to your own satisfaction whether they are suitable for your needs, production, your intended uses and applications. Such analysis adopted to the conditions of the use and application should include at least application tests, technical feasibility of the suggested solutions, taking into account safety requirements, health and environmental issues.

Unless otherwise specified in writing, our products are offered under our applicable Standard Terms and Conditions of Sale available on our website. Any information, including technical assistance, is provided without warrant and can change at any time without notice. The parties explicitly agree that the Customer accepts and explicitly releases us from any liability in tort, contract or otherwise, for any loss or damage arising from the use of our products, information or technical assistance. Any declarations and recommendations other than stated herein are not valid or binding. Nothing in this document is intended to be a recommendation to use any product in violation of patent claims concerning material of intended use.