ROKOLUB FR T-32

CHEMICAL NAME	*tert*-butylphenyl-phenyl phosphate (Reaction mass of p-t-butylphenyldiphenyl phosphate and bis(p-t-butylphenyl) phenyl phosphate and triphenyl phosphate)
CAS NUMBER	68937-40-6
FUNCTION	Fire resistant hydraulic fluid (HFDR type)
TECHNICAL REQUIREMENTS	Appearance at 20-25°C ..... homogenous, clear liquid Acid Value, mgKOH/g ..... max 0.1 Density at 25°C, g/mL ..... 1.14-1.19 ISO Viscosity Grade ..... 32 Water Content, % (w/w) ..... max 0.1
GENERAL DATA	Flash Point, °C ..... min 230 Autoignition Point, °C ..... min 500 Compatible elastomers ..... PTFE, EPDM, fluorocarbon rubber, silicone rubber, butyl rubber Self-extinguishing
APPLICATION	Rokolub FR T-32 due to unique fire resistance properties is the best available option in applications with high potential risk of fire. Especially suitable for power generation industry as well as in many general industrial application.

Information presented herein has been given in good faith and to the best of our current knowledge and experience.
The compliance of specific properties of the supplied product with the data given herein and its fitness for the intended purpose should be checked before the product is used. The producer reserves the right to modify the information presented herein as a result of technological development and improvement of the product by the producer.

PCC Rokita SA
ul. Sienkiewicza 4
56-120 Brzeg Dolny
Polska
www.pcc.rokita.pl