

## Roksol MS

<b>CHEMICAL NAME</b>	Mixture of surfactants and corrosion inhibitors
<b>TECHNICAL REQUIREMENTS</b>	<p>Appearance ..... yellow to dark brown liquid of thick oily consistance</p> <p>Total alkalinity calculate on triethanolamine, % (m/m) ..... max. 35</p> <p>Foaming ability in destilated water, ml..... max. 100</p> <p>Stability of 2% solution after 24h at 20÷30°C ..... suitable</p> <p>pH of 2% solution..... 8.0 ÷ 10.0</p> <p>Viscosity of 2% solution at 25°C, mPa·s ..... max. 5</p>
<b>GENERAL DATA</b>	<p>Solubility in water..... at any proportion</p> <p>Odor..... characteristic</p> <p>Density at 30°C, g/ml ..... approx. 1.04</p> <p>Solidification point, °C ..... below - 10</p> <p>Flash point, °C ..... above 150</p>
<b>APPLICATION</b>	Liquid used for washing and degreasing of car components.

Information presented herein has been given in good faith and to the best of our current knowledge and experience.  
The compliance of specific properties of the supplied product with the data given herein and its fitness for the intended purpose  
should be checked before the product is used. The producer reserves the right to modify the information presented herein  
as a result of technological development and improvement of the product by the producer.

**PCC Exol SA**  
ul. Sienkiewicza 4  
56-120 Brzeg Dolny  
Poland

[www.exol.pl](http://www.exol.pl)